

# Starter Switch Side instructions EN

Here is how to switch the laterality of your Starter CQB.

🕒 This process should take 10 minutes.

For video setup, [you can check our YouTube tutorial Playlists.](#)

This tutorial shows right-handed to left-handed. Left-handed to right-handed use the same steps, you will just need to follow them in mirror.

Make sure you work in a clear area and be very careful. Some parts can easily be lost.

## STEP 1: FASTENED TO MAGNETIC CUP

---

---



Remove the fastened cup using the bigger Allen key, and detach the magnetic cup.  
*Keep all parts, you will need them to assemble the cup back.*



Exchange the position of both connections.  
*The butterfly screws must be on the same side.*



Unscrew the black support on the fastened cup using the medium Allen key.  
*Be careful not to lose the square nut on the back of the cup.*



Remove the magnet from the cup using the smaller Allen key, and screw it to the other cup.  
*Be careful not to lose the square nut here too.*



You now have your magnetic cup for the other hand.

## STEP 2: MAGNETIC TO FASTENED CUP

---



You removed the magnet on the previous step. Screw the black support back on the cup that has no magnet.  
*Take care not to lose the square nut.*



Put the screw with the O-ring back on the black support.



Place the notched washer on the screw.



Slot them in the T-connection.

Place the second O-ring in the hole,  
around the screw.

Place the hex nut. Screw them all  
together.



Now you can attach the magnetic cup back.

**And there you have your left-handed Starter CQB.**

---

Revision #7

Created 24 April 2025 11:16:18 by jon

Updated 30 October 2025 15:15:43 by Sephooth